

**RENDERING**

Abbildung kann abweichen

PEAK SERIE

Das neue PEAK – zu Deutsch Gipfel – bringt einen genau da hin. Dieses Allmountain-Bike hat 150 Millimeter Federweg und ist mit 29-Zoll-Rädern ausgerüstet. Es ist wie geschaffen für Gipfelstürmer. Die moderne Geometrie macht lange Anstiege angenehm und spart Kräfte für die Abfahrt. Dafür ist die PEAK-Serie gemacht. Sie überzeugt mit einem verspielten Lenkverhalten und Fahrspass pur. Mit diesem Bike meistert man jeden Alpencross und dank Federwegreserven mit viel Sicherheit. Da dürfen eine 12-Gang-Schaltung und potente Bremsen nicht fehlen.

EINSATZBEREICH



PREIS (CHF)

4'090.-

HIGHLIGHTS

- Rock Shox Revelation RC Federgabel 150mm
- Rock Shox Deluxe Select + RT Federbein
- Shimano Deore 12-fach-Schaltgruppe
- Shimano BR-MT500 Bremsen
- Sunringlé Duroc 30 Comp Laufradsatz
- Kind Shock Rage-i Teleskopstütze

CARBON 150mm 29" SIMILIXL TBA




SPEZIFIKATIONEN

GÄNGE	12-SPEED	KURBELGARNITUR	SHIMANO FC-MT512, 2-PIECE CRANKSET, S: 30 THEETH, OTHERS 32 TEETH
RAHMEN	TRAIL GEOMETRY, FULL CARBON FRAME, 140MM TRAVEL, DROPOUT 148X12MM BOOST, 29"	INNENLAGER	SHIMANO SM-BB52
RAHMENGRÖSSE	S,M,L,XL	SATTELSTÜTZE	KIND SHOCK RAGE- I, S: 100MM, M: 125MM, L: 150MM, XL: 170MM TRAVEL, SHIMANO REMOTE, 31.6MM
GABEL	ROCK SHOX REVELATION RC, 15X110MM AXLE, TAPERED, 150MM TRAVEL, REBOUND, COMPRESSION TO LOCK	SATTEL	BIXS VL-1831
DÄMPFER	ROCK SHOX DELUXE SELECT+ RT, DEBON AIR, 2 POS LEVER, 230X57.5, HARDWARE: 30/20MMX8MM	FELGEN	SUNRINGLE WHEELSET DUROC 30 COMP, TLR, 32 HOLES, INNER WIDTH 27MM, 29"
VORBAU	BIXS 0° ANGLE, 35MM CLAMP	VORDER NABE	SUNRINGLE WHEELSET DUROC 30 COMP, 32 HOLES, 15X110MM THRU AXLE
STEUERSATZ	ACROS CUSTOMIZED FOR INTEGRATED CABLE ROUTING, 1.5" BLOCK LOCK	HINTER NABE	SUNRINGLE WHEELSET DUROC 30 COMP, 32 HOLES, 12X148MM BOOST, THRU AXLE
LENKER	BIXS RIZER BAR, 780MM, 9° BACKSWEEP, 15MM RISE, 35MM	KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
SCHALTWERK	SHIMANO DEORE RD-M6100 SGS SHADOW PLUS DESIGN, 12-SPEED	KETTE	SHIMANO CN-M6100 12-SPEED
KETTENFÜHRUNG	MRP CHAINGUIDE ISCG-05	VORDER REIFEN	ONZA IBEX, KEVLAR FOLDABLE, TUBELESS READY, 29X2.4"
SCHALTHEBEL	SHIMANO DEORE SL-M6100, CLAMP TYPE	HINTER REIFEN	ONZA IBEX, KEVLAR FOLDABLE, TUBELESS READY, 29X2.4"
BREMSHEBEL	SHIMANO BL-MT501	ARTIKELNUMMER	101-506-2042
BREMSEN	SHIMANO BR-MT500, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:180MM ROTORS		

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	370	566	90	440	77.4	65.4	1179	40	612	430	336	165
M	400	598	100	440	77.4	65.4	1213	40	620	459	336	170
L	430	632	115	440	77.4	65.4	1250	40	634	489	336	170
XL	490	666	135	450	77.4	65.4	1288	50	652	520	336	170



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL