

**RENDERING**

Abbildung kann abweichen

SIGN SERIE

Sign bedeutet «Zeichen» und genau das setzt diese Serie. Diese Trail-Bikes haben 130 Millimeter Federweg an der Front und 120 am Heck. Dank 29-Zoll-Laufrädern werden ruppige Abfahrten genauso spielend gemeistert wie kurvenreiche Flowtrails. Wer lange und anspruchsvolle Tagestouren liebt, hat mit dem leichten SIGN den passenden Partner an der Seite. Die MARIPOSA-Damenmodelle haben geschlechterspezifische Anbauteile. Alle Bikes sind mit Teleskopstützen und zeitgemässen 1×12-Schaltungen ausgestattet.

HIGHLIGHTS

- Rock Shox Pike Select Charger Federgabel 130mm
- Rock Shox SID Luxe Select Federbein
- Shimano XT 12-fach-Schaltgruppe
- Shimano XT 4-Kolben-Bremsen
- DT Swiss Spline XM-1700 Laufradsatz
- Onza Porcupine 29x2.4" Reifen

EINSATZBEREICH



PREIS (CHF)

4'490.-

ALU 130mm 29" ✓ SIMILIXL TBA




SPEZIFIKATIONEN

GÄNGE	12-SPEED
RAHMEN	TRAIL GEOMETRY, ALLOY 6061, 120MM TRAVEL, DROPOUT FOR 148X12MM BOOST, 29"
RAHMENGRÖSSE	S,M,L,XL
GABEL	ROCK SHOX PIKE SELECT CHARGER, 15X110MM AXLE, TAPERED, 130MM TRAVEL, REBOUND, COMPRESSION
DÄMPFER	ROCK SHOX SID LUXE SELECT+ WITH DT SWISS REMOTE LEVER, 165X45, 22.2X8MM HARDWARE, 2 POS OPEN/LOCK
VORBAU	FSA NS ICR STEM, 10° ANGLE, 31.8MM CLAMP
STEUERSATZ	FSA NO.55R 1.5" / ICR / STD
LENKER	RACE FACE TURBINE, 760MM, 0.5" RSIER WIDE, 31.8MM
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV
BREMSHEBEL	SHIMANO XT BL-M8100, ISPEC EV
BREMSEN	SHIMANO XT BR-M8120, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:180MM, R:180MM ROTORS, ICE TECH
KURBELGARNITUR	SHIMANO XT FC-M8100-1, HOLLOWTECH II, 32 TEETH
INNENLAGER	SHIMANO SM-BB52

SATTELSTÜTZE	KIND SHOCK LEV SI, S: 100MM, M & L: 125MM, XL: 150MM TRAVEL, SHIMANO REMOTE LEVER, 31.6MM
SATTEL	BIXS VL-1A47
FELGEN	DT SWISS WHEELSET SPLINE XM-1700, 28 HOLES, 30MM INNER WIDTH 29"
VORDER NABE	DT SWISS WHEELSET SPLINE XM-1700, 28 HOLES, 15MM THRU AXLE
HINTER NABE	DT SWISS WHEELSET SPLINE XM-1700, 28 HOLES, 12X148MM BOOST, THRU AXLE
KASSETTE	SHIMANO CS-M8100, 10-51 THEETH, 12-SPEED
KETTE	SHIMANO CN-M8100 12-SPEED
VORDER REIFEN	ONZA PORCUPINE, KEVLAR FOLDABLE, TUEBELESS READY, 29X2.40"
HINTER REIFEN	ONZA PORCUPINE, KEVLAR FOLDABLE, TUEBELESS READY, 29X2.40"
ARTIKELNUMMER	101-506-2048

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	390	573	100	435	74	67	1122	50	605	400	--	170
M	420	596	110	435	74	67	1154	50	614	420	--	175
L	460	617	115	435	74	67	1167	50	619	440	--	175
XL	500	645	125	435	74	67	1195	50	628	465	--	175



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL