



Abbildung kann abweichen

SIGN SERIE

Sign bedeutet «Zeichen» und genau das setzt diese Serie. Diese Trail-Bikes haben 130 Millimeter Federweg an der Front und 120 am Heck. Dank 29-Zoll-Laufrädern werden ruppige Abfahrten genauso spielend gemeistert wie kurvenreiche Flowtrails. Wer lange und anspruchsvolle Tagestouren liebt, hat mit dem leichten SIGN den passenden Partner an der Seite. Die MARIPOSA-Damenmodelle haben geschlechterspezifische Anbauteile. Alle Bikes sind mit Teleskopstützen und zeitgemässen 1×12-Schaltungen ausgestattet.

HIGHLIGHTS

- Fox 34 Float Rythm Federgabel 130mm
- Fox Float DPS Performance Elite Federbein
- Shimano Deore 12-fach-Schaltgruppe
- Shimano Deore BR-M6120/BR-M6100 Bremsen
- DT Swiss Spline M-1900 Laufräder
- Onza Porcupine 29x2.4" Reifen

EINSATZBEREICH



PREIS (CHF)

4'690.-

CARBON 130mm 29" WOMEN SIMIL 13.5kg




SPEZIFIKATIONEN

GÄNGE	12-SPEED
RAHMEN	TRAIL GEOMETRY, CARBON, ALLOY ROCKER. 120MM TRAVEL, 29"
RAHMENGRÖSSE	S,M,L
GABEL	FOX 34 FLOAT RHYTHM 29", 15X110MM AXLE, TAPERED, GRIP, TRAVEL: 130MM, SWEEP ADJUST LEVER
DÄMPFER	FOX FLOAT DPS PERFORMANCE ELITE, LV, EVOL, 2 POS REMOTE, TRUNION 165X45, 25MM X 8MM HARDWARE
VORBAU	RACE FACE AEFFECT, 6°ANGLE, 35MM CLAMP
STEUERSATZ	STSF17 INTEGRATED WITH CABLE INTEGRAGTION AND CABLE ENTRY DUSTCAP 1.5" UPPER AND LOWER BEARING
LENKER	RACE FACE AEFFECT, 760MM, 20MM RISE, 8° BACKSWEEP, 35MM
SCHALTWERK	SHIMANO DEORE RD-M6100 SGS SHADOW PLUS DESIGN, 12-SPEED
SCHALTHEBEL	SHIMANO DEORE SL-M6100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV
BREMSHEBEL	SHIMANO BL-M6100, ISPEC EV
BREMSEN	SHIMANO DEORE BR-M6120/BR-M6100, HYDRAULIC DISC BRAKE WITH RESIN PADS, 180MM ROTORS
KURBELGARNITUR	SHIMANO DEORE FC-6100, 32 TEETH

INNENLAGER	SHIMANO BB-MT800
SATTELSTÜTZE	KIND SHOCK LEV SI, S: 100MM, M & L: 125MM TRAVEL, SHIMANO REMOTE LEVER, 31.6MM
SATTEL	ERGON SM10 SPORT WOMEN
FELGEN	DT SWISS WHEELSET SPLINE M-1900 TLR, 28 HOLES, INNER WIDTH 30MM, 29"
VORDER NABE	DT SWISS WHEELSET SPLINE M-1900, 28 HOLES, 15X110MM THRU AXLE
HINTER NABE	DT SWISS WHEELSET SPLINE M-1900, 28 HOLES, 12X148MM BOOST, THRU AXLE
KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
KETTE	SHIMANO CN-M6100 12-SPEED
VORDER REIFEN	ONZA PORCUPINE, KEVLAR FOLDABLE, TUEBELESS READY, 29X2.40"
HINTER REIFEN	ONZA PORCUPINE, KEVLAR FOLDABLE, TUEBELESS READY, 29X2.40"
ARTIKELNUMMER	101-506-2052

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	380	558	90	437	74°	67°	1122	60	599	395	--	170
M	420	587	100	437	74°	67°	1151	60	608	420	--	175
L	460	610	110	437	74°	67°	1175	60	618	440	--	175



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm
FAHRRADGRÖSSE	S	M	L

NOTIZEN / FIRMENSTEMPEL