

**RENDERING**

Abbildung kann abweichen

PEAK-E

ENTER NEW AREAS.

Technische Trails in grossen Höhen und auf entlegenen Gipfeln sind dein Ziel, wenn du dich für das PEAK-E entscheidest. Das neue PEAK-E basiert auf dem neuen LANE-E und wurde als leichteres Paket genau für solche Missionen konzipiert. Das PEAK-E steht für Free Touring wie kein anderes Bike. Genau wie beim LANE-E unterstützt dich der starke Yamaha-PWX3-Motor zusammen mit einer 630-Wh-Batterie, um neue Ziele und epische Trails zu erreichen.

EINSATZBEREICH



ENDURO

TRAIL

CROSS COUNTRY

HIGHLIGHTS

- Yamaha PW-X3 Motor mit 630-Wh-Akku
- Rock Shox 35 Silver TK Federgabel 150mm
- Rock Shox Deluxe Select RT Federbein
- Shimano Deore 12-fach-Schaltgruppe
- Shimano BR-MT420 4-Kolben-Bremsen
- Sunringlé Duroc 37SD Comp Laufradsatz

PREIS (CHF)

5'890.-

150mm

29"

85Nm

630Wh

25km/h

A

✓

SIMILIXL

TBA




SPEZIFIKATIONEN

GÄNGE	12-SPEED	KURBELGARNITUR	FSA CK320, ISIS, BOOST, STEEL CHAINRING, 34 TEETH
RAHMEN	E-TRAIL GEOMETRY, ALLOY 6061, 140MM TRAVEL, ALLOY ROCKER, DROPOUT 148X12MM BOOST, 29"	SATTELSTÜTZE	KIND SHOCK RAGEI, S: 100MM, M: 125MM, L: 150MM, XL: 170MM TRAVEL, WESTY LEVER REMOTE, 31.6MM
RAHMENGRÖSSE	S,M,L,XL	SATTEL	BIXS VL-3575
GABEL	ROCK SHOX 35 SILVER TK SOLO AIR 29", 15X110MM AXLE, TAPERED, 150MM TRAVEL, REBOUND, COMP. TO LOCK	FELGEN	SUNRINGLE WHEELSET DUROC 37SD COMP, TLR, 32 HOLES, INNER WIDTH 32MM, 29"
DÄMPFER	ROCK SHOX DELUX SELECT+ RT, LEVER, 185X55MM, TRUNNION MOUNT, HARDWARE: 20MMX8MM	VORDER NABE	SUNRINGLE WHEELSET DUROC 37SD COMP, 32 HOLES, 15X110MM THRU AXLE
VORBAU	BIXS 0° ANGLE, 35MM CLAMP	HINTER NABE	SUNRINGLE WHEELSET DUROC 37SD COMP, 32 HOLES, 12X148MM BOOST, THRU AXLE
STEUERSATZ	ACROS CUSTOMIZED FOR INTEGRATED CABLE ROUTING, 1.5" BLOCK LOCK	KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
LENKER	BIXS RIZER BAR, 780MM, 9° BACKSWEEP, 15MM RISE, 35MM	KETTE	KMC E12 SPORT, EPT ANTI-RUST
SCHALTWERK	SHIMANO DEORE RD-M6100 SGS SHADOW PLUS DESIGN, 12-SPEED	VORDER REIFEN	ONZA IBEX, KEVLAR FOLDABLE, TUBELESS READY, 29X2.6"
KETTENFÜHRUNG	MRP CUSTOM BIXS MOUNT 32-38 TEETH	HINTER REIFEN	ONZA IBEX, KEVLAR FOLDABLE, TUBELESS READY, 29X2.6"
SCHALTHEBEL	SHIMANO DEORE SL-M6100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	MOTOR	YAMAHA PW-X 3 SERIES, 250 WATT
BREMSHEBEL	SHIMANO BL-M4100, ISPEC EV	BATTERIE	SIMPLO, 36V, 630WH
BREMSEN	SHIMANO BR-MT420, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:203MM, R:203MM ROTORS	REICHWEITE	MAX. 150KM
		DISPLAY	YAMAHA DISPLAY A
		ARTIKELNUMMER	101-506-3005

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	390	586	110	450	76°	65°	1207	35	627	430	355	165
M	430	602	115	450	76°	65°	1224	35	631	445	355	165
L	475	618	120	450	76°	65°	1241	35	636	460	355	165
XL	500	644	125	450	76°	65°	1268	35	640	485	355	165



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL