


SPEZIFIKATIONEN

GÄNGE	12-SPEED	KURBELGARNITUR	SHIMANO STEPS FC-EM600, 34 TEETH
RAHMEN	E-TRAIL GEOMETRY, ALLOY 6061, 130MM TRAVEL, ALLOY ROCKER, DROPOUT 148X12MM BOOST, 29"	SATTELSTÜTZE	FOX TRANSFER FACTORY KASHIMA, S: 100MM, M & L: 125MM, XL: 150MM TRAVEL, REMOTE, 30.9MM
RAHMENGRÖSSE	S,M,L,XL	SATTEL	ERGON SM10 E-MOUNTAIN SPORT MEN
GABEL	FOX 34 FLOAT FACTORY 29", KASHIMA, 15X110MM AXLE, TAPERED, FIT4, TRAVEL: 130MM, 3-POSITION LEVER	FELGEN	DT SWISS WHEELSET SPLINE HX 1501 TLR, INNER WIDTH 30MM, 29"
DÄMPFER	FOX FLOAT DPS FACTORY, KASHIMA, LV, EVOL, 3 POS LEVER, 205MM, TRUNNION MOUNT, HARDWARE: 30MMX8MM	VORDER NABE	DT SWISS WHEELSET SPLINE HX-1501, 15X110MM THRU AXLE
VORBAU	RACE FACE TURBINE R, 0° ANGLE, 35MM CLAMP	HINTER NABE	DT SWISS WHEELSET SPLINE HX-1501, 12X148MM BOOST, THRU AXLE
STEUERSATZ	FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER	KASSETTE	SHIMANO CS-M8100, 10-51 THEETH, 12-SPEED
LENKER	RACE FACE TURBINE R, 780MM, 20MM RISE, 8° BACKSWEEP, 35MM	KETTE	SHIMANO CN-M8100 12-SPEED
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED	SCHEINWERFER	LITEMOVE 350 LUX
KETTENFÜHRUNG	SHIMANO CHAIN DEVICE CD-EM800	RÜCKLICHT	INFINI 5 MODES REAR LIGHT
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	VORDER REIFEN	SCHWALBE WICKED WILL EVO SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.4"
BREMSHEBEL	SHIMANO XT BL-M8100, ISPEC EV	HINTER REIFEN	SCHWALBE WICKED WILL EVO SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.4"
BREMSEN	SHIMANO XT BR-M8120, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:203MM, R:203MM ROTORS, ICE TECH	MOTOR	SHIMANO STEPS EP8, 250 WATT
		BATTERIE	DARFON, 36V, 630WH
		REICHWEITE	MAX. 140KM
		DISPLAY	SHIMANO SC-EM800
		ARTIKELNUMMER	101-506-3015

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	406	590	135	470	74°	66°	1196	40	633	408	340	165
M	445	595	140	470	74°	66°	1202	50	638	413	340	165
L	480	615	145	470	74°	66°	1223	60	643	431	340	165
XL	530	635	150	470	74°	66°	1243	70	648	450	340	165



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE 149–163 cm 159–178 cm 174–188 cm 185–200 cm

FAHRRADGRÖSSE S M L XL

NOTIZEN / FIRMENSTEMPEL