



Abbildung kann abweichen

SIGN-E

TRAILS, TRAILS, TRAILS.

Entdecke deinen Flow auf langen Trailtouren. Durch die sensible Sensorik und die individuelle Einstellbarkeit ist der Shimano-EP8-Motor für sein natürliches Fahrgefühl bekannt. Lass dich in den Flow-Zustand versetzen und genieße die ausgewogenen Fahreigenschaften des SIGN-E.

HIGHLIGHTS

- Shimano Steps EP8 Motor mit 630-Wh-Akku
- Fox 36 Float Performance Federgabel 130mm
- Fox Float DPS Performance Elite Federbein
- Shimano XT 12-fach-Schaltgruppe
- Shimano SLX 4-Kolben-Bremsen
- DT Swiss Spline H-1900 Laufradsatz

EINSATZBEREICH



PREIS (CHF)

6'790.-

130mm 29" 85Nm 630Wh 25km/h SC-EM800 ✓ SIMILIXL 24.4kg




Release 08/2022 / intercycle ag / Änderungen vorbehalten

SPEZIFIKATIONEN

GÄNGE	12-SPEED	SATTELSTÜTZE	KIND SHOCK LEV INTEGRA, S: 65MM, M: 100MM, L: 125MM, XL: 150MM TRAVEL, REMOTE, 30.9MM
RAHMEN	E-TRAIL GEOMETRY, ALLOY 6061, 130MM TRAVEL, ALLOY ROCKER, DROPOUT 148X12MM BOOST, 29"	SATTEL	ERGON SM10 E-MOUNTAIN SPORT MEN
RAHMENGRÖSSE	S,M,L,XL	FELGEN	DT SWISS WHEELSET SPLINE H-1900 TLR, 28 HOLES, INNER WIDTH 35MM, 29"
GABEL	FOX 36 FLOAT PERFORMANCE, 15X110MM AXLE, TAPERED, GRIP, TRAVEL: 130MM, 3-POSITION LEVER	VORDER NABE	DT SWISS WHEELSET SPLINE H-1900, 28 HOLES, 15X110MM THRU AXLE
DÄMPFER	FOX FLOAT DPS PERFORMANCE ELITE, LV, EVOL, 3 POS LEVER, 205X60MM, TRUNNION MOUNT, HARDWAR: 30MMX8MM	HINTER NABE	DT SWISS WHEELSET SPLINE H-1900, 28 HOLES, 12X148MM BOOST, THRU AXLE
VORBAU	RACE FACE AEFFECT R, 0° ANGLE, 35MM CLAMP	KASSETTE	SHIMANO CS-M7100, 10-51 THEETH, 12-SPEED
STEUERSATZ	FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER	KETTE	SHIMANO CN-M8100 12-SPEED
LENKER	RACE FACE AEFFECT R, 780MM, 20MM RISE, 8° BACKSWEEP, 35MM	VORDER REIFEN	SCHWALBE NOBBY NIC EVO SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.6"
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED	HINTER REIFEN	SCHWALBE NOBBY NIC EVO SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.6"
KETTENFÜHRUNG	SHIMANO CHAIN DEVICE CD-EM800	MOTOR	SHIMANO STEPS EP8, 250 WATT
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	BATTERIE	DARFON, 36V, 630WH
BREMSHEBEL	SHIMANO SLX BL-M7100, ISPEC EV	REICHWEITE	MAX. 140KM
BREMSEN	SHIMANO SLX BR-M7120, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:203MM, R:203MM ROTORS	DISPLAY	SHIMANO SC-EM800
KURBELGARNITUR	SHIMANO STEPS FC-EM600, 34 TEETH	ARTIKELNUMMER	101-506-3016

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	406	590	135	470	74°	66°	1196	40	633	408	340	165
M	445	595	140	470	74°	66°	1202	50	638	413	340	165
L	480	615	145	470	74°	66°	1223	60	643	431	340	165
XL	530	635	150	470	74°	66°	1243	70	648	450	340	165



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE 149–163 cm 159–178 cm 174–188 cm 185–200 cm

FAHRRADGRÖSSE S M L XL

NOTIZEN / FIRMENSTEMPEL