



Abbildung kann abweichen

SIGN-E

TRAILS, TRAILS, TRAILS.

Entdecke deinen Flow auf langen Trailtouren. Durch die sensible Sensorik und die individuelle Einstellbarkeit ist der Shimano-EP8-Motor für sein natürliches Fahrgefühl bekannt. Lass dich in den Flow-Zustand versetzen und genieße die ausgewogenen Fahreigenschaften des SIGN-E.

HIGHLIGHTS

- Shimano Steps EP8 Motor mit 630-Wh-Akku
- Rock Shox 35 Gold RL Debonair Federgabel 130mm
- Rock Shox Deluxe Select R Federbein
- Shimano SLX 12-fach-Schaltgruppe
- Shimano BR-M6120 4-Kolben-Bremsen
- Schwalbe Nobby Nic und Hans Dampf 29x2.6" Reifen

EINSATZBEREICH



ENDURO

TRAIL

CROSS COUNTRY

PREIS (CHF)

5'790.-

130mm

29"

85Nm

630Wh

25km/h

SC-E5003

✓

SIMILIXL

24.9kg




Release 08/2022 / intercycle ag / Änderungen vorbehalten

SPEZIFIKATIONEN

GÄNGE	12-SPEED	KURBELGARNITUR	SHIMANO STEPS FC-EM600, 34 TEETH
RAHMEN	E-TRAIL GEOMETRY, ALLOY 6061, 130MM TRAVEL, ALLOY ROCKER, DROPOUT 148X12MM BOOST, 29"	SATTELSTÜTZE	KIND SHOCK RAGEI, M: 100MM, L: 125MM, XL: 150M TRAVEL, SHIMANO REMOTE LEVER, 30.9MM
RAHMENGRÖSSE	S,M,L,XL	SATTEL	ERGON SM10 E-MOUNTAIN SPORT MEN
GABEL	ROCK SHOX 35 GOLD RL DEBONAIR 29", 15X110MM AXLE, TAPERED, 130MM TRAVEL, REBOUND, COMP.TO LOCK	FELGEN	ALEXRIMS EM-35, 32 HOLES, INNER WIDTH 35MM, 29"
DÄMPFER	ROCK SHOX DELUX SELECT R, LEVER, DEBON AIR, 205MM, TRUNNION MOUNT, HARDWARE: 30MM X 8MM	VORDERE NABE	SHIMANO HB-TC500-15-B, 32 HOLES, 15X110MM BOOST THRU AXLE
VORBAU	BIXS 0° ANGLE, 35MM CLAMP	HINTERE NABE	SHIMANO FH-TC600-MS-B, 32 HOLES, 12X148MM BOOST THRU AXLE
STEUERSATZ	FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER	KASSETTE	SHIMANO CS-M7100, 10-51 THEETH, 12-SPEED
LENKER	BIXS RIZER BAR, 780MM, 9° BACKSWEEP, 15MM RISE, 35MM	KETTE	SHIMANO CN-M7100 12-SPEED
SCHALTWERK	SHIMANO SLX RD-M7100 SGS SHADOW PLUS DESIGN, 12-SPEED	VORDER REIFEN	SCHWALBE NOBBY NIC EVO SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.6"
KETTENFÜHRUNG	SHIMANO CHAIN DEVICE CD-EM800	HINTER REIFEN	SCHALBE HANS DAMPF, SUPER TRAIL, ADDIX SPEEDGRIP, TL EASY, 29X2.6"
SCHALTHEBEL	SHIMANO SLX SL-M7100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	MOTOR	SHIMANO STEPS EP8, 250 WATT
BREMSHEBEL	SHIMANO BL-M6100, ISPEC EV	BATTERIE	DARFON, 36V, 630WH
BREMSEN	SHIMANO BR-M6120, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:203MM, R:203MM ROTORS	REICHWEITE	MAX. 140KM
		DISPLAY	SHIMANO SC-E5003
		ARTIKELNUMMER	101-506-3017

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	406	590	135	470	74°	66°	1196	40	633	408	340	165
M	445	595	140	470	74°	66°	1202	50	638	413	340	165
L	480	615	145	470	74°	66°	1223	60	643	431	340	165
XL	530	635	150	470	74°	66°	1243	70	648	450	340	165



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL