



Abbildung kann abweichen

CAMPUS-E

STADT – LAND – FLUSS.

Immer unter Strom, immer unterwegs. Im Alltag möchtest du möglichst rasch und komfortabel von A nach B kommen und am Wochenende möglichst weit um den nächsten See. Das CAMPUS-E ist ein hochwertiges Elektrofahrrad mit integrierter Unterstützung und allem, was du dir für eine komfortable Fahrt auf dem Velo wünschst. Kraftvolle Shimano-Steps-EP-8-Motoren und 630- oder 500-Wh-Akkus. Aufsteigen, losfahren und entspannt ankommen.

EINSATZBEREICH



TOUR

ACTIVE

CITY

HIGHLIGHTS

- Shimano Steps EP8 Motor mit 630-Wh-Akku
- Suntour Mobie 25 Air Federgabel
- Shimano RD-M5130 10-fach-Schaltgruppe
- Shimano BR-MT420 4-Kolben-Bremsen
- Trelock Bike I Airflow Lichtenlage
- Schwalbe Energizer Plus Performance 700x55c Reifen

PREIS (CHF)

4'590.-

75mm

700C

85Nm

630Wh

25km/h

SC-E6100

✓

SIMIL

26.8kg




SPEZIFIKATIONEN

| | | | |
|----------------|--|---------------|---|
| GÄNGE | 10-SPEED | FELGEN | ALEXRIMS DM-21, 32 HOLES, INNER WIDTH 21MM, 700C |
| RAHMEN | E-TOURING CONCEPT, ALLOY 6061, 700C | VORDER NABE | SHIMANO HB-TC500-15, 32 HOLES, 15X100MM THRU AXLE |
| RAHMENGRÖSSE | S,M,L | HINTER NABE | SHIMANO FH-TC500-HM, 32 HOLES, 12X142MM THRU AXLE |
| GABEL | SUNTOUR MOBIE 25 AIR, 700C, TAPERED, 15X100MM AXLE, 75MM TRAVEL, LOCKOUT | KASSETTE | SHIMANO CS-LG600, 11-43 THEETH, 10-SPEED |
| VORBAU | ERGOTEC SEPIA AHEAD 50, ANGLE ADJUSTABLE, 31.8MM CLAMP | KETTE | SHIMANO CN-LG500 10-SPEED |
| STEUERSATZ | FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER | VORDER REIFEN | SCHWALBE ENERGIZER PLUS, PERFORMANCE, GREEN-GUARD ADDIX 700X55C |
| LENKER | BIXS HB-RB12L RIZER BAR, 720MM, 15° ANGLE, 15MM RISE, 31.8MM | HINTER REIFEN | SCHWALBE ENERGIZER PLUS, PERFORMANCE, GREEN-GUARD ADDIX 700X55C |
| SCHALTWERK | SHIMANO RD-M5130 GS SHADOW PLUS DESIGN, 10-SPEED | GEPÄCKTRÄGER | MASSLOAD BIXS CUSTOM WITH INTEGRATED REAR LIGHT |
| SCHALTHEBEL | SHIMANO SL-M5130, WITH OPTICAL GEAR DISPLAY | SCHUTZBLECHE | BIXS ALLOY FENDER, 62MM WIDE, 700C |
| BREMSHEBEL | SHIMANO BL-MT402-3A | SCHEINWERFER | TRELOCK BIKE-I AIRFLOW, LS-780 LED, 100 LUX |
| BREMSEN | SHIMANO BR-MT420, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:180MM, R:180MM ROTORS | RÜCKLICHT | HERRMANS INTEGRATED REAR LIGHT ON CARRIER |
| KURBELGARNITUR | SHIMANO STEPS FC-EM600, 38 TEETH | MOTOR | SHIMANO STEPS EP8, 250 WATT |
| PEDALE | VP 831, INLEAD GRIP TREAD | BATTERIE | DARFON, 36V, 630WH |
| SATTELSTÜTZE | BIXS SP-3D2, 350MM, 31.6MM | REICHWEITE | MAX. 140KM |
| SATTEL | ERGON ST10 | DISPLAY | SHIMANO SC-E6100 |
| | | ARTIKELNUMMER | 101-506-3042 |

GEOMETRIE

| SIZE | A | B | C | D | E | F | G | H | I | J | K | L |
|------|-----|-----|-----|-----|-----|-----|------|----|-----|-----|-----|-----|
| S | 440 | 590 | 180 | 460 | 74° | 69° | 1136 | 90 | 678 | 405 | 300 | 170 |
| M | 480 | 595 | 180 | 460 | 74° | 69° | 1146 | 90 | 678 | 410 | 300 | 170 |
| L | 520 | 600 | 180 | 460 | 74° | 69° | 1154 | 90 | 678 | 415 | 300 | 170 |



| | |
|---|------------------------|
| A | Rahmengrösse |
| B | Oberrohr horizontal mm |
| C | Steuerrohr mm |
| D | Kettenstreben mm |
| E | Sitzwinkel Grad |
| F | Steuerrohrwinkel Grad |
| G | Radstand mm |
| H | Vorbau mm |
| I | Stack mm |
| J | Reach mm |
| K | Tretlagerhöhe mm |
| L | Kurbellänge |

GRÖSSENRECHNER

KÖRPERGRÖSSE 147–163 cm 159–178 cm 174–188 cm

FAHRRADGRÖSSE S M L

NOTIZEN / FIRKENSTEMPEL