



Abbildung kann abweichen

CAMPUS-E

STADT – LAND – FLUSS.

Immer unter Strom, immer unterwegs. Im Alltag möchtest du möglichst rasch und komfortabel von A nach B kommen und am Wochenende möglichst weit um den nächsten See. Das CAMPUS-E ist ein hochwertiges Elektrofahrrad mit integrierter Unterstützung und allem, was du dir für eine komfortable Fahrt auf dem Velo wünschst. Kraftvolle Shimano-Steps-EP-8-Motoren und 630- oder 500-Wh-Akkus. Aufsteigen, losfahren und entspannt ankommen.

EINSATZBEREICH



TOUR

ACTIVE

CITY

HIGHLIGHTS

- Shimano Steps EP8 Motor mit 630-Wh-Akku
- Suntour Mobie 25 Air Federgabel
- Shimano RD-M5130 10-fach-Schaltgruppe
- Shimano BR-MT420 4-Kolben-Bremsen
- Trelock Bike I Airflow Lichtanlage
- Schwalbe Energizer Plus Performance 700x55c Reifen

PREIS (CHF)

4'590.-

75mm

700C

85Nm

630Wh

25km/h

SC-E6100

✓

SIMIL

27.6kg




SPEZIFIKATIONEN

GÄNGE	10-SPEED	FELGEN	ALEXRIMS DM-21, 32 HOLES, INNER WIDTH 21MM, 700C
RAHMEN	E-TOURING CONCEPT, ALLOY 6061, DI 700C	VORDER NABE	SHIMANO HB-TC500-15, 32 HOLES, 15X100MM THRU AXLE
RAHMENGRÖSSE	S, M, L	HINTER NABE	SHIMANO FH-TC500-HM, 32 HOLES, 12X142MM THRU AXLE
GABEL	SUNTOUR MOBIE 25 AIR, 700C, TAPERED, 15X100MM AXLE, 75MM TRAVEL, LOCKOUT	KASSETTE	SHIMANO CS-LG600, 11-43 THEETH, 10-SPEED
VORBAU	ERGOTEC SEPIA AHEAD 50, ANGLE ADJUSTABLE, 31.8MM CLAMP	KETTE	SHIMANO CN-LG500 10-SPEED
STEUERSATZ	FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER	VORDER REIFEN	SCHWALBE ENERGIZER PLUS, PERFORMANCE, GREEN-GUARD ADDIX 700X55C
LENKER	BIXS HB-RB12L RIZER BAR, 700MM, 15° ANGLE, 25MM RISE, 31.8MM	HINTER REIFEN	SCHWALBE ENERGIZER PLUS, PERFORMANCE, GREEN-GUARD ADDIX 700X55C
SCHALTWERK	SHIMANO RD-M5130 GS SHADOW PLUS DESIGN, 10-SPEED	GEPÄCKTRÄGER	MASSLOAD BIXS CUSTOM WITH INTEGRATED REAR LIGHT
SCHALTHEBEL	SHIMANO SL-M5130, WITH OPTICAL GEAR DISPLAY	SCHUTZBLECHE	BIXS ALLOY FENDER, 62MM WIDE, 700C
BREMSHEBEL	SHIMANO BL-MT402-3A	SCHEINWERFER	TRELOCK BIKE-I AIRFLOW, LS-780 LED, 100 LUX
BREMSEN	SHIMANO BR-MT420, 4-PISTON HYDRAULIC DISC BRAKE, RESIN PADS, F:180MM, R:180MM ROTORS	RÜCKLICHT	HERRMANS INTEGRATED REAR LIGHT ON CARRIER
KURBELGARNITUR	SHIMANO STEPS FC-EM600, 38 TEETH	MOTOR	SHIMANO STEPS EP8, 250 WATT
PEDALE	VP 831, INLEAD GRIP TREAD	BATTERIE	DARFON, 36V, 630WH
SATTELSTÜTZE	BIXS SP-3D2, 350MM, 31.6MM	REICHWEITE	MAX. 140KM
SATTEL	ERGON ST10	DISPLAY	SHIMANO SC-E6100
		ARTIKELNUMMER	101-506-3043

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	440	580	180	480	73°	67°	1150	90	674	370	300	170
M	480	590	180	480	73°	67°	1165	90	674	383	300	170
L	520	600	180	480	73°	67°	1172	90	674	391	300	170



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE 147–163 cm 159–178 cm 174–188 cm

FAHRRADGRÖSSE S M L

NOTIZEN / FIRKENSTEMPEL