CORE 100



RENDERING
Abbildung kann abweichen

CORE

GO HARD!

Das CORE ist deine Eintrittskarte in den Mountainbike-Sport.
Erlebe den Fahrspass auf flowigen Trails und ausgiebigen Touren.

HIGHLIGHTS

· Rock Shox SID SL Federgabel 100mm
· Shimano XT 12-fach-Schaltgruppe
· Shimano BR-MT410 Bremsen
. Schwalbe Racing Ray und Racing Ralph 29x2.35" Reifen
· Alexrims MD-30 Laufradsatz

EINSATZBEREICH

TRAIL | CROSS COUNTRY | TOUR

PREIS (CHF)

2'490.–

CARBON 100mm 29" SIMILIXL 11.5kg

Release 08/2022 / intercycle ag / Änderungen vorbehalten

SPEZIFIKATIONEN

GÄNGE	12-SPEED
RAHMEN	SPORT GEOMETRY, SUPERLITE CARBON M40, 12X148MM BOOST DROPOUT, HARDTAIL 29"
RAHMENGRÖSSE	S,M,L,XL
GABEL	ROCK SHOX SID SL 29", DEBONAIR, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT
VORBAU	BIXS AS-M03, 0°ANGLE, 31.8MM CLAMP
STEUERSATZ	FSA NO.42/48 ACB, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 8.7MM TOP COVER
LENKER	BIXS HB-RB12W RIZER BAR, 760MM, 9°ANGLE, 25MM RISE, 31.8MM
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV
BREMSHEBEL	SHIMANO BL-M4100, ISPEC EV
BREMSEN	SHIMANO BR-MT410, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:160MM ROTORS
KURBELGARNITUR	SHIMANO FC-MT511, 2-PIECE CRANKSET, 32 TEETH

INNENLAGER	SHIMANO SM-BB52
PEDALE	WELLGO WPD-823, WITH CLEAT
SATTELSTÜTZE	BIXS SP-719, S & M: 350MM, OTHERS: 400MM, 30.9MM
SATTEL	BIXS VL-3533
FELGEN	ALEXRIMS MD-30, 32 HOLES, INNER WIDTH 30MM, 29"
VORDER NABE	SHIMANO HB-TC500-15-B, 32 HOLES, 15X110MM BOOST THRU AXLE
HINTER NABE	SHIMANO FH-TC500-MS-B, 32 HOLES, 12X148MM BOOST THRU AXLE
KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
KETTE	SHIMANO CN-M6100 12-SPEED
VORDER REIFEN	SCHWALBE RACING RAY EVO SUPER RACE, ADDIX SPEEDGRIP, TL EASY, 29X2.35"
HINTER REIFEN	SCHWALBE RACING RALPH EVO SUPER RACE, ADDIX SPEEDGRIP, TL EASY, 29X2.35"
ARTIKELNUMMER	101-506-3076

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	400	579	95	430	74°	68.5°	1091	60	608	405	310	170
M	430	603	95	430	74°	68.5°	1115	70	608	430	310	175
L	472	633	110	430	74°	68.5°	1146	70	622	455	310	175
XL	520	662	125	430	74°	68.5°	1176	80	636	480	310	175



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL

WWW.BIXS.COM

Release 08/2022 / intercycle ag / Änderungen vorbehalten