


RENDERING

Abbildung kann abweichen

CORE

GO HARD!

Das CORE ist deine Eintrittskarte in den Mountainbike-Sport. Erlebe den Fahrspass auf flowigen Trails und ausgiebigen Touren.

HIGHLIGHTS

- Rock Shox Judy Silver TK Federgabel 100mm
- Shimano SLX 12-fach-Schaltgruppe
- Shimano BR-MT410 Bremsen
- Schwalbe Smart Sam K-Guard 29x2.35" Reifen
- 29-Zoll-Laufräder mit Shimano-Naben

EINSATZBEREICH



PREIS (CHF)

1'599.-

ALU 100mm 29" ✓ SIMILIXL 13.6 kg




SPEZIFIKATIONEN

GÄNGE	12-SPEED	KURBELGARNITUR	SHIMANO FC-MT511, 2-PIECE CRANKSET, 32 TEETH
RAHMEN	SPORT GEOMETRY ALLOY 6061 HYDROF. T.B., DROPOUT 148X12MM BOOST, HARDTAIL 29"	INNENLAGER	SHIMANO SM-BB52
RAHMENGRÖSSE	S,M,L,XL	PEDALE	WELLGO C-015
GABEL	ROCK JUDY SILVER TK 29", SOLO AIR SPRING, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT	SATTELSTÜTZE	BIXS SP-719, S & M: 350MM, OTHERS: 400MM, 31.6MM
VORBAU	BIXS AS-M03, 0° ANGLE, 31.8MM CLAMP	SATTEL	BIXS VL-3533
STEUERSATZ	FSA NO.57B, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 8.2MM TOP COVER	FELGEN	ALEXRIMS MD-30, 32 HOLES, INNER WIDTH 30MM, 29"
LENKER	BIXS HB-RB12L, 740MM, 9° ANGLE, 25MM RISE, 31.8MM	VORDER NABE	SHIMANO HB-TC500-15-B, 32 HOLES, 15X110MM BOOST THRU AXLE
SCHALTWERK	SHIMANO SLX RD-M7100 SGS SHADOW PLUS DESIGN, 12-SPEED	HINTER NABE	SHIMANO FH-TC500-MS-B, 32 HOLES, 12X148MM BOOST THRU AXLE
SCHALTHEBEL	SHIMANO DEORE SL-M6100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV	KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
BREMSHEBEL	SHIMANO BL-M4100, ISPEC EV	KETTE	SHIMANO CN-M6100 12-SPEED
BREMSEN	SHIMANO BR-MT410, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:180MM ROTORS	VORDER REIFEN	SCHWALBE SMART SAM K-GUARD, 29X2.35"
		HINTER REIFEN	SCHWALBE SMART SAM K-GUARD, 29X2.35"
		ARTIKELNUMMER	101-506-3078

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	380	570	105	455	73.5°	68	1114	35	619	387	308	170
M	430	590	105	455	73.5°	68	1134	45	619	407	308	175
L	480	610	110	455	73.5°	68	1154	55	624	425	308	175
XL	530	630	120	455	73.5°	68	1175	65	633	443	308	175



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL