

**RENDERING**

Abbildung kann abweichen

CORE

GO HARD!

Das CORE ist deine Eintrittskarte in den Mountainbike-Sport. Erlebe den Fahrspass auf flowigen Trails und ausgiebigen Touren.

HIGHLIGHTS

- Rock Shox Judy Silver TK Federgabel 100mm
- Shimano SLX 12-fach-Schaltgruppe
- Shimano BR-MT410 Bremsen
- Schwalbe Smart Sam K-Guard 29x2.35" Reifen
- 29-Zoll-Laufräder mit Shimano-Naben

EINSATZBEREICH



PREIS (CHF)

1'599.-

ALU 100mm 29" ✓ SIMILIXL 13.6 kg




SPEZIFIKATIONEN

GÄNGE	12-SPEED
RAHMEN	SPORT GEOMETRY ALLOY 6061 HYDROF. T.B., DROPOUT 148X12MM BOOST, HARDTAIL 29"
RAHMENGRÖSSE	S,M,L,XL
GABEL	ROCK JUDY SILVER TK 29", SOLO AIR SPRING, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT
VORBAU	BIXS AS-M03, 0°ANGLE, 31.8MM CLAMP
STEUERSATZ	FSA NO.57B, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 8.2MM TOP COVER
LENKER	BIXS HB-RB12L, 740MM, 9°ANGLE, 25MM RISE, 31.8MM
SCHALTWERK	SHIMANO SLX RD-M7100 SGS SHADOW PLUS DESIGN, 12-SPEED
SCHALTHEBEL	SHIMANO DEORE SL-M6100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV
BREMSHEBEL	SHIMANO BL-M4100, ISPEC EV
BREMSEN	SHIMANO BR-MT410, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:180MM ROTORS

KURBELGARNITUR	SHIMANO FC-MT511, 2-PIECE CRANKSET, 32 TEETH
INNENLAGER	SHIMANO SM-BB52
PEDALE	WELLGO C-015
SATTELSTÜTZE	BIXS SP-719, S & M: 350MM, OTHERS: 400MM, 31.6MM
SATTEL	BIXS VL-3533
FELGEN	ALEXRIMS MD-30, 32 HOLES, INNER WIDTH 30MM, 29"
VORDER NABE	SHIMANO HB-TC500-15-B, 32 HOLES, 15X110MM BOOST THRU AXLE
HINTER NABE	SHIMANO FH-TC500-MS-B, 32 HOLES, 12X148MM BOOST THRU AXLE
KASSETTE	SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED
KETTE	SHIMANO CN-M6100 12-SPEED
VORDER REIFEN	SCHWALBE SMART SAM K-GUARD, 29X2.35"
HINTER REIFEN	SCHWALBE SMART SAM K-GUARD, 29X2.35"
ARTIKELNUMMER	101-506-3079

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
S	380	570	105	455	73.5°	68	1114	35	619	387	308	170
M	430	590	105	455	73.5°	68	1134	45	619	407	308	175
L	480	610	110	455	73.5°	68	1154	55	624	425	308	175
XL	530	630	120	455	73.5°	68	1175	65	633	443	308	175



A Rahmengrösse

B Oberrohr horizontal mm

C Steuerrohr mm

D Kettenstreben mm

E Sitzwinkel Grad

F Steuerrohrwinkel Grad

G Radstand mm

H Vorbau mm

I Stack mm

J Reach mm

K Tretlagerhöhe mm

L Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	149–163 cm	159–178 cm	174–188 cm	185–200 cm
FAHRRADGRÖSSE	S	M	L	XL

NOTIZEN / FIRMENSTEMPEL