



**RENDERING**  
Abbildung kann abweichen

## CORE

GO HARD!

Das CORE ist deine Eintrittskarte in den Mountainbike-Sport. Erlebe den Fahrspass auf flowigen Trails und ausgiebigen Touren.

## HIGHLIGHTS

- Rock Shox Judy Silver TK Federgabel 100mm
- Shimano Deore 12-fach-Schaltgruppe
- Shimano BR-MT200 Bremsen
- Schwalbe Smart Sam K-Guard 29x2.35" Reifen
- 29-Zoll-Laufräder mit Shimano-Naben

## EINSATZBEREICH



PREIS (CHF)

**1'299.-**

ALU    100mm    29"    ✓    SIMILIXL    13.9 kg




## SPEZIFIKATIONEN

|              |  |                |   |
|--------------|--|----------------|---|
| GÄNGE        | 12-SPEED   | KURBELGARNITUR | SHIMANO FC-MT511, 2-PIECE CRANKSET, 32 TEETH              |
| RAHMEN       | SPORT GEOMETRY ALLOY 6061 HYDROF. T.B., DROPOUT 148X12MM BOOST, HARDTAIL 29"                     | INNENLAGER     | SHIMANO SM-BB52   |
| RAHMENGRÖSSE | S,M,L,XL   | PEDALE         | WELLGO C-015  |
| GABEL        | ROCK JUDY SILVER TK 29", SOLO AIR SPRING, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT | SATTELSTÜTZE   | BIXS SP-3D2, S & M: 350MM, OTHERS: 400MM, 31.6MM          |
| VORBAU       | BIXS AS-M03, 0° ANGLE, 31.8MM CLAMP  | SATTEL         | BIXS VL-3533  |
| STEUERSATZ   | FSA NO.57B, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 8.2MM TOP COVER                             | FELGEN         | ALEXRIMS MD-30, 32 HOLES, INNER WIDTH 30MM, 29"           |
| LENKER       | BIXS HB-RB12L, 740MM, 9° ANGLE, 25MM RISE, 31.8MM  | VORDER NABE    | SHIMANO HB-TC500-15-B, 32 HOLES, 15X110MM BOOST THRU AXLE |
| SCHALTWERK   | SHIMANO DEORE RD-M6100 SGS SHADOW PLUS DESIGN, 12-SPEED  | HINTER NABE    | SHIMANO FH-TC500-MS-B, 32 HOLES, 12X148MM BOOST THRU AXLE |
| SCHALTHEBEL  | SHIMANO DEORE SL-M6100, WITH OPTICAL GEAR DISPLAY  | KASSETTE       | SHIMANO CS-M6100, 10-51 THEETH, 12-SPEED                  |
| BREMSHEBEL   | SHIMANO BL-MT201   | KETTE          | SHIMANO CN-M6100 12-SPEED                                 |
| BREMSEN      | SHIMANO BR-MT200, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:180MM ROTORS                  | VORDER REIFEN  | SCHWALBE SMART SAM K-GUARD, 29X2.35"                      |
|              |  | HINTER REIFEN  | SCHWALBE SMART SAM K-GUARD, 29X2.35"                      |
|              |  | ARTIKELNUMMER  | 101-506-3081  |

## GEOMETRIE

| SIZE | A   | B   | C   | D   | E     | F  | G    | H  | I   | J   | K   | L   |
|------|-----|-----|-----|-----|-------|----|------|----|-----|-----|-----|-----|
| S    | 380 | 570 | 105 | 455 | 73.5° | 68 | 1109 | 35 | 629 | 383 | 308 | 170 |
| M    | 430 | 590 | 105 | 455 | 73.5° | 68 | 1129 | 45 | 629 | 404 | 308 | 175 |
| L    | 480 | 610 | 110 | 455 | 73.5° | 68 | 1150 | 55 | 634 | 422 | 308 | 175 |
| XL   | 530 | 630 | 120 | 455 | 73.5° | 68 | 1171 | 65 | 643 | 439 | 308 | 175 |



|   |                        |
|---|------------------------|
| A | Rahmengrösse           |
| B | Oberrohr horizontal mm |
| C | Steuerrohr mm          |
| D | Kettenstreben mm       |
| E | Sitzwinkel Grad        |
| F | Steuerrohrwinkel Grad  |
| G | Radstand mm            |
| H | Vorbau mm              |
| I | Stack mm               |
| J | Reach mm               |
| K | Tretlagerhöhe mm       |
| L | Kurbellänge            |

## GRÖSSENRECHNER

|               |            |            |            |            |
|---------------|------------|------------|------------|------------|
| KÖRPERGRÖSSE  | 149–163 cm | 159–178 cm | 174–188 cm | 185–200 cm |
| FAHRRADGRÖSSE | S          | M          | L          | XL         |

NOTIZEN / FIRNENSTEMPEL