



Abbildung kann abweichen

SPLASH

DER SCHULWEG MACHT AB HEUTE SPASS.

Ein Trail Bike, das dich sicher zu Schule bringt und bereit ist, zusammen mit dir erste Trail-Erfahrungen zu sammeln. An dein erstes Trail Bike wirst du dich immer erinnern!

HIGHLIGHTS

- Suntour SF15 XCM Federgabel 100mm
- Shimano Deore 10-Gang-Schaltung
- Shimano BR-MT200 Bremsen
- Schwalbe Rapid Rob 27.5x2.25" Reifen
- Laufräder mit Shimano-Naben

EINSATZBEREICH



CROSS COUNTRY

TOUR

ACTIVE

PREIS (CHF)

959.-

ALU 100mm 27.5" ✓ XSISIMIL 13.5kg




SPEZIFIKATIONEN

GÄNGE	10-SPEED
RAHMEN	SPORT GEOMETRY ALLOY 6061 HYDROF. T.B. HARDTAIL 27.5"
RAHMENGRÖSSE	XS,S,M,L
GABEL	SUNTOUR SF15, XCM, HLO-DS 27.5" COIL SPRING, 100MM TRAVEL, HYDRAULIC LOCKOUT
VORBAU	BIXS AS-M03, 0° ANGLE, 31.8MM CLAMP
STEUERSATZ	FSA NO.57B, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 8.2MM TOP COVER
LENKER	BIXS HB-RB12L, 740MM, 9° ANGLE, 25MM RISE, 31.8MM
SCHALTWERK	SHIMANO DEORE RD-M5120 SGS SHADOW PLUS DESIGN, 10-SPEED
SCHALTHEBEL	SHIMANO DEORE SL-M4100, WITH OPTICAL GEAR DISPLAY
BREMSHEBEL	SHIMANO BL-MT201
BREMSEN	SHIMANO BR-MT200, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:180MM, R:180MM ROTORS
KURBELGARNITUR	SHIMANO FC-M5100-1, 2-PIECE CRANKSET, 32 TEETH
INNENLAGER	SHIMANO SM-BB52
PEDALE	VP 990S

SATTELSTÜTZE	BIXS SP-3D2, XS: 300MM, S & M: 350MM, ORTHERS: 400MM, 31.6MM
SATTEL	BIXS VL-3533
FELGEN	ALEXRIMS MD-19, 32 HOLES, INNER WIDTH 19MM, 27.5"
VORDER NABE	SHIMANO HB-RM35, 32 HOLES, QR
HINTER NABE	SHIMANO FH-RM35, 32 HOLES, QR
KASSETTE	SHIMANO CS-M4100, 11-46 THEETH, 10-SPEED
KETTE	SHIMANO CN-HG54
VORDER REIFEN	SCHWALBE RAPID ROB, K-GUARD 27.5X2.25"
HINTER REIFEN	SCHWALBE RAPID ROB, K-GUARD 27.5X2.25"
ARTIKELNUMMER	101-506-3095

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K	L
XS	350	550	105	440	73°	69°	1059	35	598	367	300	170
S	380	560	110	440	73°	69°	1070	35	602	375	300	170
M	430	580	120	440	73°	69°	1090	45	612	392	300	175
L	480	600	130	440	73°	69°	1110	55	622	410	300	175



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm
L	Kurbellänge

GRÖSSENRECHNER

KÖRPERGRÖSSE	135–153cm	149–163cm	159–178cm	174–188cm
FAHRRADGRÖSSE	XS	S	M	L

NOTIZEN / FIRMENSTEMPEL