

SILEX 400

MOD. 41389

MATT BLUE (BLACK)



LITE Leichter Rahmen aus Aluminium 6066, dreifach endverstärkte Hydroforming-Rohre. Gravel-Geometrie für laufruhiges, dabei agiles Lenkverhalten und aufrechte Sitzposition. Mit interner Zugverlegung und „Press-Fit 86“-Tretlagergehäuse.

| COMMUTING | FITNESS | GRAVEL | OFF ROAD |



RAHMEN	SILEX LITE, material: aluminium, 700x38C / 650Bx45C max. WHS, 100x12/142x12mm axle standard, BB86 bottom bracket standard
GRÖSSEN	XS(44cm), S(47), M(50), L(53), XL(56)
GABEL	MERIDA SILEX CF2, Tapered, material: carbon, 700x38C / 650Bx45C max. wheelsize
UMWERFER	Shimano GRX400
SCHALTHEBEL VORNE	Shimano GRX400
SCHALTWERK	Shimano GRX400
SCHALTHEBEL HINTEN	Shimano GRX400
BREMSE VORNE	Shimano GRX400, Hydraulic disc / 160 mm
BREMSE HINTEN	Shimano GRX400, Hydraulic disc / 160 mm
BREMSHEBEL	Shimano GRX400
STEUERSATZ	MERIDA M2331
LENKER	MERIDA EXPERT GR, material: aluminium, 400mm (XS-S), 420mm (M), 440mm (L/XL)
VORBAU	MERIDA EXPERT CW, material: aluminium, 31.8mm diameter, -8° stem angle, 80 mm all sizes
VORBAU GRÖSSE	80 mm all sizes
GRIFFE	MERIDA ROAD EXPERT
SATTEL	MERIDA COMP CC, V-mount
SATTELSTÜTZE	MERIDA COMP CC, material: aluminium, 30.9mm diameter, 0mm setback

SATTELKLEMME	MERIDA EXPERT
KETTE	KMC X10
KURBELGARNITUR	Shimano GRX600, 46-30 teeth, 170 mm-XS/S, 172,5 mm-M, 175 mm-L/XL
KURBELARM	170 mm-XS/S, 172,5 mm-M, 175 mm-L/XL
KASSETTE	Shimano CS-HG50, 11-36 teeth, 10 speed
INNENLAGER	Shimano Pressfit BB71
LAUFRADSATZ	MERIDA COMP SL, 17mm inner width, 22mm height, material: aluminium
NABEN VORNE	VP CLK170F, 100x12mm width front hub, 32 spoke holes, centerlock
NABEN HINTEN	VP CLK270R, 142x12mm width rear hub, 32 spoke holes, centerlock
STECKACHSE VORNE	MERIDA EXPERT SL
STECKACHSE HINTEN	MERIDA EXPERT SL, including removeable lever, 6/4mm allen key
SPEICHEN	Black stainless
PNEU VORNE	Maxxis Rambler, 700x38C, fold, TR, EXO
PNEU HINTEN	Maxxis Rambler, 700x38C, fold, TR, EXO
GEWICHT	10,36 kg



PROLITE 66
TRIPLE BUTTED
ALUMINIUM



HYDRO
FORMING
SYSTEM



X-TAPER
HEADTUBE



SMOOTH
WELDING



INTERNAL
CABLE
ROUTING



DOWN TUBE
EXIT



F-MOUNT



C-MOUNT