

Numinis R2700i

SLATE BLACK



Rahmen	Numinis R intube, Material: Aluminium, 29, headset: 1.8 tapered, axle standard: 12x148 mm, Postmount 203 mm, UDH dropout
Gabel	FOX AWL eMTB+, suspension travel: 140 mm, 1.5 tapered, Rake: 44 mm
Dämpfer	FOX Float DPS Performance, suspension travel: 130 mm, 185 x 50 Trunnion, 3 Pos Lever
Schaltwerk	SHIMANO Deore XT
Bremse vorne	SHIMANO Deore 4-piston / 203 mm Centerlock
Bremse hinten	SHIMANO Deore 4-piston / 203 mm Centerlock
Sattel	PROCRAFT E-Pro
Sattelstütze	PROCRAFT DROP Pro, diameter: 30.9 mm, Hub: 125 mm (S), 150 mm (M), 170 mm (L, XL)
Lenker	PROCRAFT Trail Pro 35 ICR, diameter: 35 mm, width: 760 mm, Rise: 20 mm
Vorbau	PROCRAFT Trail Expert 35 AICR
Kurbelgarnitur	CENTURION Deluxe Gen4 34T
Kassette	SHIMANO Deore XT, CS-LG600-11, 11-50T
Felgen	PROCRAFT Altitude MD30, IW 30 mm, tubeless ready
Pneus	MAXXIS Dissector, 29x2.4 WT, tubeless ready, 120TPI, 3C MaxxTerra, EXO+ // MAXXIS Dissector, 29x2.4 WT, tubeless ready, 120TPI, 3C MaxxTerra, EXO+
Motor	BOSCH Performance Line CX BES 3
Display	BOSCH Kiox
Batterie	750 Wh