

CENTURION 

E-Fire Tour R2600i

INFRARED



Rahmen	E-Fire Tour R G4 intube, Material: Aluminium, 28, headset: 1.5 straight, axle standard: 10x135 mm, Postmount 180 mm
Gabel	SR SUNTOUR MOBIE25 AIR LOR, suspension travel: 63 mm, 1.5 tapered
Schaltwerk	SHIMANO Deore XT
Bremse vorne	SHIMANO BR-MT410 / 180 mm Centerlock
Bremse hinten	SHIMANO BR-MT410 / 180 mm Centerlock
Sattel	PROCRAFT Tour II
Sattelstütze	PROCRAFT Pro, diameter: 30.9 mm, Länge: 350 mm
Lenker	PROCRAFT Riser Pro, diameter: 31.8 mm, width: 640 mm (S), 680 mm (M, L, XL), Rise: 22 mm
Vorbau	PROCRAFT Comp II
Kurbelgarnitur	PROCRAFT Comp 42T incl. BG
Kassette	SHIMANO Deore, CS-M5100-11, 11-42T
Felgen	PROCRAFT MPD23, IW 23 mm
Pneus	SCHWALBE Marathon GT, 28x2.0, Performance Line mit Reflex // SCHWALBE Marathon GT, 28x2.0, Performance Line mit Reflex
Gewicht	24.9 kg
Motor	BOSCH Performance Line CX Gen4
Display	BOSCH Kiox
Batterie	625 Wh